Application No.:

10/036,716

Amendment Dated:

October 27, 2005 Reply to Office Action of: July 28, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- (Currently Amended) An image reading device for reading an optical 1. image of a plurality of components using a camera having pixels arrayed in a line, the image reading device comprising:
- a pixel-selecting section for accessing the pixels individually and outputting an image signal;
- a processing-computing section for 1) setting a plurality of image taken-(b) in areas based on mounting data and component data, 2) outputting pixel-selecting information for selecting pixels individually from among the pixels, based on widths of the respective image-taken-in areas, and 3) setting respective start and stop timing of the image signal;
- a relative-moving mechanism for moving the plurality of components (c) relative to the camera;
- a relative-movement detector for 1) detecting the plurality of (d) components moving a given distance in one direction relative to the camera by comparing position information from the relative-moving mechanism with each of the respective taken-in areas to determine whether each of the components is within the taken-in area and 2) providing a movement-detecting signal; and
- a controller for controlling said pixel-selecting section based on the (e) pixel-selecting information and outputting a pixel signal supplied from the pixel specified by the pixel-selecting information when said relative-movement detector receives the movement detecting signal-,

wherein the widths of the image-taken-in areas correspond to movement of the plurality of components, respectively, in the one direction relative to the camera, and

MAT-8213US

Application No.:

10/036,716

Amendment Dated: Reply to Office Action of: July 28, 2005

October 27, 2005

the camera has a scanning width that accommodates the largest component.

2. (Cancelled).

(Currently Amended) The image reading device of claim 1, wherein the 3. pixels form a line sensor having a sample-hold section, first and second shift gates, a photoelectric transfer element, and a reset-drain.

- (Currently Amended) An image reading method for reading an optical 4. image of a plurality of components using a camera with pixels arrayed in a line, said method comprising the steps of:
- setting a plurality of image-taken-in areas based on mounting data and (a) component data;
- generating pixel-selecting information based on widths of respective (b) image-taken-in areas;
 - setting respective start and stop timing of the image signal; (c)
- moving the plurality of components by a relative-moving mechanism in (d) one direction relative to a camera;
- determining whether each of the components is within the respective taken-in area by comparing position information from the relative moving mechanism with each of respective taken-in-areas; and
- outputting an image signal from a specified pixel repeatedly based on (f) the pixel-selecting information when each of the components moves a given distance relative to the camera when it is determined to be within the respective taken-inarea.,

wherein the widths of the image-taken-in areas correspond to movement of the plurality of components, respectively, in the one direction relative to the camera, and

the camera includes a scanning width that accommodates the largest component.

MAT-8213US

Application No.: 10/036,716
Amendment Dated: October 27, 2005
Reply to Office Action of: July 28, 2005

5.-8. (Cancelled).